

CENTRE DIRECT

XEROX

External Print Server

**CONNECT WITH
XEROX QUALITY**



- **Share printing resources with multiple users**
- **Compatible with a wide variety of printers, copier/printers and all-in-ones**
- **Supports multiple operating systems**



DIGITAL
THE DOCUMENT COMPANY
XEROX

External Print Server

SPECIFICATIONS

Dimensions (WxDxH)	2.4" x 3.5" x 1.1" / 62 x 88 x 28 mm
Weight	0.38 lbs. / .083 kg
Power	Universal Power Supply 110-220VAC, 50/60Hz input

NETWORK OPERATING SYSTEMS

Microsoft	Windows 95, 98 and 98 Second Edition, 2000, NT Server and Workstation 4.0
Novell NetWare	NetWare 3.1x and 4.1x (with year 2000 patches), 3.2, 4.2, and 5.1 Supports Bindery Emulation, NDS, and NDPS. PServer print method
Unix	SunOS, Solaris 2.5.1/2.6, Solaris 7, HP-UX 10.x/11.x, IBM AIX 4.2/4.3, SCO Unixware 7, DEC Unix 4.2, SGI 6.x, Red Hat Linux 6.x
IBM	OS/2 Warp 4, OS/2 Warp 4 Server and Advanced Server
MAC	Mac OS 8.0+

PROTOCOLS

Microsoft Windows	TCP/IP (Telnet, LPR, FTP, DHCP, WINS, SNMP) IPX (with NetWare, SNMP) NetBEUI (SMB-NBF)
Novell NetWare	IPX (NCP with NDS, SAP, RIP, auto-frame type sensing for IEEE802.2, IEEE802.3, SNAP, and Ethernet II frame types) TCP/IP (DHCP, LPR)
UNIX	TCP/IP (LPR, FTP, UDP, Telnet, DHCP, BOOTP, RARP, ARP, SNMP, TFTP)
MAC	Apple EtherTalk Phase 1 or 2 TCP/IP (LPR, FTP, DHCP)
IBM OS/2	TCP/IP (LPR, FTP, DHCP, WINS, SNMP) IPX (with NetWare, SNMP) NetBEUI (SMB-NBF)

PORTS

1 — Network	10BaseT, RJ-45 Connector, Category 3 or 5, 10 Mbps Ethernet
1 — Parallel	IEEE 1284 Centronics, Bi-directional and nibble modes

INSTALLATION AND MANAGEMENT

XEROX CentreWare	CentreWare DP (Novell NetWare, TCP/IP) CentreWare SUNOS/ Solaris Services
XEROX PrinterMap	Windows 95/98/NT 4.0/2000 Compatible with CentreWare DP, MarkVision, JetAdmin and PhaserLink
Windows Network Neighborhood	Easy set-up in Windows 95/98/NT 4.0/2000 using NetBEUI for peer-to-peer printing
Telnet	All Windows, UNIX, Apple, and OS/2 Systems
IP Set Utility	Makes setting IP addresses easier in TCP/IP Windows environments
LPR Printing Client	Makes assigning a PC port easier in TCP/IP Windows environments

REGULATORY / SAFETY

FCC Class B, UL 1950
CSA 22.2 No. 950, EN60950
CE: EN55022 Class B
EN50082 — 1

OPERATING ENVIRONMENT

Temperature	40° to 105° F / 5° to 40° C
Humidity	10% to 95% RH
Power Consumption	< 6 W

PRODUCTIVE

- Share printing resources – inkjet and laser; printers, copier/printers and all-in-ones
- Allows users to send print jobs from multiple PCs

CONVENIENT AND FLEXIBLE

- Supports:
 - Novell Netware
 - Unix
 - Windows
 - EtherTalk
 - and more
- No additional installation software needed with most Windows operating systems
- Install printers anywhere—not just near a PC
- Provides printer management solutions for small office, home office and enterprise environments

XEROX RELIABILITY

- Xerox Support & Service
- Xerox Warranty

DIGITAL
THE DOCUMENT COMPANY

XEROX

